



	SuperSport 950	SuperSport 950 S
ENGINE		
TYPE	Testastretta 11°, L-Twin cylinder, 4 valve per cylinder, Desmodromic, liquid cooled	Testastretta 11°, L-Twin cylinder, 4 valve per cylinder, Desmodromic, liquid cooled
DISPLACEMENT	937 cc	937 cc
BORE X STROKE	94 x 67.5 mm	94 x 67.5 mm
COMPRESSION RATIO	12,6± 0.5 :1	12,6± 0.5 :1
POWER	81 kW (110 hp) @ 9.000 rpm	81 kW (110 hp) @ 9.000 rpm
TORQUE	93 Nm (69 lb-ft) @ 6.500 rpm	93 Nm (69 lb-ft) @ 6.500 rpm
FUEL INJECTION	Electronic fuel injection system, 53 mm throttle bodies with full Ride-by-Wire	Electronic fuel injection system, 53 mm throttle bodies with full Ride-by-Wire
EXHAUST	Lightweight 2-1-2 system with catalytic converter and two lambda probes. Twin aluminium mufflers	Lightweight 2-1-2 system with catalytic converter and two lambda probes. Twin aluminium mufflers
TRANSMISSION		
GEARBOX	6 speed with Ducati Quick Shift (DQS) up/down EVO	6 speed with Ducati Quick Shift (DQS) up/down EVO
PRIMARY DRIVE	Straight cut gears; Ratio 1.84:1	Straight cut gears; Ratio 1.84:1
RATIO	1=37/15 2=30/17 3=28/20 4=26/22 5=24/23 6=23/24	1=37/15 2=30/17 3=28/20 4=26/22 5=24/23 6=23/24
FINAL DRIVE	Chain; Front sprocket 15; Rear sprocket 43	Chain; Front sprocket 15; Rear sprocket 43
CLUTCH	Slipper and self-servo wet multiplate clutch with hydraulic control. Self bleeding master cylinder.	Slipper and self-servo wet multiplate clutch with hydraulic control. Self bleeding master cylinder.
CHASSIS		
FRAME	Tubular steel Trellis frame attached to the chylinders head	Tubular steel Trellis frame attached to the chylinders head
FRONT SUSPENSION	Fully adjustable Æ 43 mm usd Marzocchi fork	Fully adjustable Æ 48 mm usd Öhlins fork with TiN treatment
FRONT WHEEL	Y shaped, 3-spoke in light alloy 3.50" x 17"	Y shaped, 3-spoke in light alloy 3.50" x 17"
FRONT TYRE	Pirelli Diablo Rosso III 120/70 ZR17	Pirelli Diablo Rosso III 120/70 ZR17
REAR SUSPENSION	Progressive linkage with adjustable Sachs monoshock. Aluminium single-sided swingarm	Progressive linkage with fully adjustable Öhlins monoshock. Aluminium single-sided swingarm
REAR WHEEL	Y shaped, 3-spoke in light alloy 5.50" x 17"	Y shaped, 3-spoke in light alloy 5.50" x 17"
REAR TYRE	Pirelli Diablo Rosso III 180/55 ZR17	Pirelli Diablo Rosso III 180/55 ZR17
WHEEL TRAVEL (FRONT/REAR)	130 mm (5.1 in)/144 mm (5.7 in)	130 mm (5.1 in)/144 mm (5.7 in)
FRONT BRAKE	2 x 320 mm semi-floating discs, radially mounted Monobloc Brembo M4-32 callipers, 4-piston, radial pump with Bosch Cornering ABS. Self bleeding master cylinder	2 x 320 mm semi-floating discs, radially mounted Monobloc Brembo M4-32 callipers, 4-piston, radial pump with Bosch Cornering ABS. Self bleeding master cylinder
REAR BRAKE	245 mm disc, 2-piston caliper, Bosch Cornering ABS	245 mm disc, 2-piston caliper, Bosch Cornering ABS
INSTRUMENTATION	Full-TFT color display	Full-TFT color display
DIMENSIONS AND WEIGHTS		
DRY WEIGHT	184 kg (405 lb)	184 kg (405 lb)
KERB WEIGHT*	210 kg (463 lb)	210 kg (463 lb)
SEAT HEIGHT	810 mm (31.9 in)	810 mm (31.9 in)
WHEELBASE	1.478 mm (58.3 in)	1.478 mm (58.3 in)
RAKE	24°	24°
TRAIL	91 mm (3.6 in)	91 mm (3.6 in)
FUEL TANK CAPACITY	16 l - 4.2 gallon (US)	16 l - 4.2 gallon (US)
NUMBER OF SEATS	2	2
EQUIPMENT		
SAFETY EQUIPMENT	Riding Modes, Bosch Cornering ABS , Ducati Traction Control (DTC) EVO, Ducati Wheelie Control (DWC) EVO.	Riding Modes, Bosch Cornering ABS , Ducati Traction Control (DTC) EVO, Ducati Wheelie Control (DWC) EVO.
STANDARD EQUIPMENT	Power Modes, Day Time Running Light (DRL)**, Full-TFT color display, Adjustable windscreen, Ducati Quick Shift (DQS) up/down EVO,	Power Modes, Day Time Running Light (DRL)**, Full-TFT color display, Adjustable windscreen, Öhlins suspension, Ducati Quick Shift (DQS) up/down EVO, Passenger seat cowl
READY FOR	Anti-theft system, Heated grips, Ducati Multimedia System (DMS)	Anti-theft system, Heated grips, Ducati Multimedia System (DMS)
WARRANTY AND MAINTENANCE		
WARRANTY	24 months unlimited mileage	24 months unlimited mileage
MAINTENANCE SERVICE INTERVALS	15.000 km - 9.000 mi/12 months	15.000 km - 9.000 mi/12 months
DESMO SERVICE	30.000 km - 18.000 mi	30.000 km - 18.000 mi
EMISSIONS AND CONSUMPTION (Only for countries where Euro 5 standard applies)		
STANDARD	Euro 5	Euro 5
CO2 EMISSIONS	134 g/km	134 g/km
CONSUMPTION	5,6 l/100 km	5,6 l/100 km

*Kerb weights indicate total bike weight with all operating consumable liquids and a fuel tank filled to 90% of capacity (as per EU Regulation 44/2014

** Not available in Canada, China, Japan