



	MULTISTRADA V2	MULTISTRADA V2 S
ENGINE		
TYPE	Ducati Testastretta, L-Twin cylinder, Desmodromic timing, 4 valves per cylinder, Liquid cooled	Ducati Testastretta, L-Twin cylinder, Desmodromic timing, 4 valves per cylinder, Liquid cooled
DISPLACEMENT	937 cc (57.2 cu in)	937 cc (57.2 cu in)
BORE X STROKE	94 x 67.5 mm	94 x 67.5 mm
COMPRESSION RATIO	12.6:1	12.6:1
POWER	113 hp (83 kW) @ 9,000 rpm	113 hp (83 kW) @ 9,000 rpm
TORQUE	96 Nm (9.8 kgm, 71 lb ft) @ 7,750 rpm 94 Nm (9.6 kgm, 69 lb ft) @ 6,750 rpm*	96 Nm (9.8 kgm, 71 lb ft) @ 7,750 rpm 94 Nm (9.6 kgm, 69 lb ft) @ 6,750 rpm*
FUEL INJECTION	Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system	Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system
EXHAUST	Stainless steel single muffler, Catalytic converter and 2 lambda probes	Stainless steel single muffler, Catalytic converter and 2 lambda probes
TRANSMISSION		
GEARBOX	6 speed	6 speed with Ducati Quick Shift up/down (DQS)
PRIMARY DRIVE	Straight cut gears; Ratio 1.84:1	Straight cut gears; Ratio 1.84:1
RATIO	1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24	1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24
FINAL DRIVE	Chain; Front sprocket 15; Rear sprocket 43	Chain; Front sprocket 15; Rear sprocket 43
CLUTCH	Slipper and self-servo wet multiplate clutch with hydraulic control	Slipper and self-servo wet multiplate clutch with hydraulic control
CHASSIS		
FRAME	Tubular steel trellis frame	Tubular steel trellis frame
FRONT SUSPENSION	Ø 48 mm fully adjustable usd fork	Ø 48 mm fully adjustable usd fork, Electronic compression and rebound damping adjustment with Ducati Skyhook Suspension Evo
FRONT WHEEL	Light alloy casted 3.0" x 19"	Light alloy casted 3.0" x 19"
FRONT TYRE	Pirelli Scorpion Trail II 120/70 ZR 19	Pirelli Scorpion Trail II 120/70 ZR 19
REAR SUSPENSION	Fully adjustable monoshock, Remote spring preload adjustment, Aluminium double-sided swingarm	Fully adjustable monoshock, Electronic compression, rebound damping and spring pre-load adjustment with Ducati Skyhook Suspension Evo, Aluminium double-sided swingarm
REAR WHEEL	Light alloy casted 4.5" x 17"	Light alloy casted 4.5" x 17"
REAR TYRE	Pirelli Scorpion Trail II 170/60 ZR 17	Pirelli Scorpion Trail II 170/60 ZR 17
WHEEL TRAVEL (FRONT/REAR)	170 mm / 170 mm (6.7 in / 6.7 in)	170 mm / 170 mm (6.7 in / 6.7 in)
FRONT BRAKE	2 x Ø 320 mm aluminum flange semi-floating discs, Radially mounted Brembo monobloc 4- piston 2-pad callipers, Radial Master Cylinder, Cornering ABS	2 x Ø 320 mm aluminum flange semi-floating discs, Radially mounted Brembo monobloc 4-piston 2-pad callipers, Radial Master Cylinder, Cornering ABS
REAR BRAKE	Ø 265 mm disc, 2-piston Brembo floating calliper, Cornering ABS	Ø 265 mm disc, 2-piston Brembo floating calliper, Cornering ABS
INSTRUMENTATION	LCD Display	5" TFT colour display
DIMENSIONS AND WEIGHTS		
DRY WEIGHT	199 kg (439 lb)	202 kg (445 lb)
KERB WEIGHT*	222 kg (489 lb)	225 kg (496 lb)
SEAT HEIGHT	830 mm (32.7 in) (850 mm (33.5 in) with high seat accessory, 810 mm (31.9 in) with low seat accessory, 790 mm (31.1 in) with low seat + low suspension kit accessory)	830 mm (32.7 in) (850 mm (33.5 in) with high seat accessory, 810 mm (31.9 in) with low seat accessory, 790 mm (31.1 in) with low seat + low suspension kit accessory)
WHEELBASE	1,594 mm (62.8 in)	1,594 mm (62.8 in)
RAKE	25°	25°
TRAIL	106 mm (4.2 in)	106 mm (4.2 in)
FUEL TANK CAPACITY	20 l (5.3 US Gal)	20 l (5.3 US Gal)
NUMBER OF SEATS	Dual seat	Dual seat
EQUIPMENT		
SAFETY EQUIPMENT	Riding Modes, Power Modes, Ducati Safety Pack (Cornering ABS, Ducati Traction Control), Ducati Brake Light, Vehicle Hold Control	Riding Modes, Power Modes, Ducati Safety Pack (Cornering ABS, Ducati Traction Control), Ducati Cornering Lights, Ducati Brake Light, Vehicle Hold Control
STANDARD EQUIPMENT	Self cancelling turn indicators	Ducati Skyhook Suspension Evo, Ducati Quick Shift up/down, Cruise control, Hands-Free, Backlit handlebar switches, 5" TFT colour display, Full LED headlight, Self cancelling turn indicators
READY FOR	Ducati Quick Shift up/down, Ducati Multimedia System, Antitheft system	Ducati Multimedia System, Tyre Pressure Monitoring System, Antitheft system
WARRANTY AND MAINTENANCE		
WARRANTY	24/48** months, Unlimited mileage	24/48** months, Unlimited mileage
MAINTENANCE SERVICE INTERVALS	15,000 km (9,000 miles) / 12 months	15,000 km (9,000 miles) / 12 months
DESMOSERVICE	30,000 km (18,000 miles)	30,000 km (18,000 miles)
EMISSIONS AND CONSUMPTION (Only for countries where Euro 5 standard applies)		
STANDARD	Euro 5	Euro 5
CO2 EMISSIONS	137 g/km	137 g/km
CONSUMPTION	5,9 l/100km	5,9 l/100km

* Only for countries where Euro 5 standard applies

** Only for countries where 4ever Multistrada warranty applies