



	Monster	Monster+	Monster SP
ENGINE			
TYPE	Testastretta 11°, V2 - 90°, 4 valves per cylinder, desmodromic valvetrain, liquid cooled	Testastretta 11°, V2 - 90°, 4 valves per cylinder, desmodromic valvetrain, liquid cooled	Testastretta 11°, V2 - 90°, 4 valves per cylinder, desmodromic valvetrain, liquid cooled
DISPLACEMENT	937 cc (57 cu in)	937 cc (57 cu in)	937 cc (57 cu in)
BORE X STROKE	94 mm x 67.5 mm	94 mm x 67.5 mm	94 mm x 67.5 mm
COMPRESSION RATIO	13.3:1	13.3:1	13.3:1
POWER	111 hp (82 kW) @ 9,250 rpm	111 hp (82 kW) @ 9,250 rpm	111 hp (82 kW) @ 9,250 rpm
TORQUE	9.5 kqm (93 Nm, 69 lb ft) @ 6,500 rpm	9.5 kqm (93 Nm, 69 lb ft) @ 6,500 rpm	9.5 kqm (93 Nm, 69 lb ft) @ 6,500 rpm
FUEL INJECTION	Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system	Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system	Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system
EXHAUST	Pre-muffler and twin muffler, catalytic converter and 2 lambda probes	Pre-muffler and twin muffler, catalytic converter and 2 lambda probes	Pre-muffler and Termignoni type approved twin muffler, catalytic converter and 2 lambda probes
TRANSMISSION			
GEARBOX	6 speed with Ducati Quick Shift up/down	6 speed with Ducati Quick Shift up/down	6 speed with Ducati Quick Shift up/down
PRIMARY DRIVE	Straight cut gears, ratio 1.85:1	Straight cut gears, ratio 1.85:1	Straight cut gears, ratio 1.85:1
RATIO	1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24	1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24	1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24
FINAL DRIVE	Chain, front sprocket z15, rear sprocket z43	Chain, front sprocket z15, rear sprocket z43	Chain, front sprocket z15, rear sprocket z43
CLUTCH	Slipper and self-servo multiplate wet clutch with hydraulic control	Slipper and self-servo multiplate wet clutch with hydraulic control	Slipper and self-servo multiplate wet clutch with hydraulic control
CHASSIS			
FRAME	Aluminum alloy Front Frame	Aluminum alloy Front Frame	Aluminum alloy Front Frame
FRONT SUSPENSION	Ø 43 mm usd fork	Ø 43 mm usd fork	Fully adjustable Öhlins NIX 30 Ø 43 mm usd front fork with TiN treatment on inner tube
FRONT WHEEL	Light alloy cast, 3.5" x 17"	Light alloy cast, 3.5" x 17"	Light alloy cast, 3.5" x 17"
FRONT TYRE	Pirelli Diablo Rosso III 120/70 ZR17	Pirelli Diablo Rosso III 120/70 ZR17	Pirelli Diablo Rosso IV 120/70 ZR17
REAR SUSPENSION	Progressive linkage, preload adjustable monoshock, aluminium double-sided swingarm	Progressive linkage, preload adjustable monoshock, aluminium double-sided swingarm	Progressive linkage, fully adjustable Öhlins monoshock, aluminium double-sided swingarm
REAR WHEEL	Light alloy cast, 5.5" x 17"	Light alloy cast, 5.5" x 17"	Light alloy cast, 5.5" x 17"
REAR TYRE	Pirelli Diablo Rosso III 180/55 ZR17	Pirelli Diablo Rosso III 180/55 ZR17	Pirelli Diablo Rosso IV 180/55 ZR17
WHEEL TRAVEL (FRONT/REAR)	130 mm / 140 mm (5.1 in / 5.5 in)	130 mm / 140 mm (5.1 in / 5.5 in)	140 mm / 150 mm (5.5 in / 5.9 in)
FRONT BRAKE	2 x Ø 320 mm semi-floating discs, radially mounted Brembo M4.32 monobloc 4-piston callipers, radial master cylinder, Cornering ABS	2 x Ø 320 mm semi-floating discs, radially mounted Brembo M4.32 monobloc 4-piston callipers, radial master cylinder, Cornering ABS	2 x Ø 320 mm semi-floating aluminum flange discs, radially mounted Brembo Stylema® monobloc 4-piston callipers, radial master cylinder, Cornering ABS
REAR BRAKE	Ø 245 mm disc, Brembo 2-piston floating calliper, Cornering ABS	Ø 245 mm disc, Brembo 2-piston floating calliper, Cornering ABS	Ø 245 mm disc, Brembo 2-piston floating calliper, Cornering ABS
INSTRUMENTATION	4.3" TFT colour display	4.3" TFT colour display	4.3" TFT colour display
DIMENSIONS AND WEIGHTS			
DRY WEIGHT	166 kg (366 lb)	166 kg (366 lb)	166 kg (366 lb)
KERB WEIGHT	188 kg (414 lb)	188 kg (414 lb)	186 kg (410 lb)
SEAT HEIGHT	820 mm (32.3 in) 840 mm (33.1 in) with high seat accessory 800 mm (31.5 in) with low seat accessory 775 mm (30.5 in) with low seat + low suspension kit accessory	820 mm (32.3 in) 840 mm (33.1 in) with high seat accessory 800 mm (31.5 in) with low seat accessory 775 mm (30.5 in) with low seat + low suspension kit accessory	840 mm (33.1 in) 850 mm (33.5 in) with high seat accessory 810 mm (31.9 in) with low seat accessory
WHEELBASE	1,474 mm (58.0 in)	1,474 mm (58.0 in)	1,472 mm (57.9 in)
RAKE	24°	24°	23°
TRAIL	93 mm (3.7 in)	93 mm (3.7 in)	87 mm (3.4 in)
FUEL TANK CAPACITY	14 l (3.7 US gal)	14 l (3.7 US gal)	14 l (3.7 US gal)
NUMBER OF SEATS	2	2	2
EQUIPMENT			
SAFETY EQUIPMENT	Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Daytime Running Light, Ducati Brake Light	Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Daytime Running Light, Ducati Brake Light	Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Daytime Running Light*, Ducati Brake Light
STANDARD EQUIPMENT	Ducati Quick Shift, Ducati Power Launch, 4.3" TFT colour display, Full LED headlight and lighting system, Dynamic turn indicators, USB power socket	Ducati Quick Shift, Ducati Power Launch, 4.3" TFT colour display, Full LED headlight and lighting system, Dynamic turn indicators, USB power socket, Flyscreen, Passenger seat cover	Ducati Quick Shift, Ducati Power Launch, 4.3" TFT colour display, Full LED headlight and lighting system, Dynamic turn indicators*, USB power socket, Flyscreen, Passenger seat cover, Brembo Stylema® callipers, Termignoni type approved twin muffler, Steering damper, Lithium-ion battery
READY FOR	Ducati Multimedia System, Heated grips	Ducati Multimedia System, Heated grips	Ducati Multimedia System, Heated grips
WARRANTY AND MAINTENANCE			
WARRANTY	24 months, unlimited mileage	24 months, unlimited mileage	24 months, unlimited mileage
MAINTENANCE SERVICE INTERVALS	15,000 km (9,000 miles) / 24 months	15,000 km (9,000 miles) / 24 months	15,000 km (9,000 miles) / 24 months
DESMOSERVICE	30,000 km (18,000 miles)	30,000 km (18,000 miles)	30,000 km (18,000 miles)
EMISSIONS AND CONSUMPTION (Only for countries where Euro 5 standard applies)			
STANDARD	Euro 5	Euro 5	Euro 5
CO2 EMISSIONS	120 g/km	120 g/km	120 g/km
CONSUMPTION	5.2 l/100 km	5.2 l/100 km	5.2 l/100 km

*Please check with your dealer product availability. Bike specifications and equipment may vary from market to market. Please refer to your local dealer for further information.