



Multistrada V4 Rally	
ENGINE	
TYPE	Ducati V4 Granturismo, V4 - 90°, 4 valves per cylinder, counter-rotating crankshaft, twin pulse firing order, semi dry sump, liqued cooled
DISPLACEMENT	1,158 cc (71 cu in)
BORE X STROKE	83 x 53,3 mm
COMPRESSION RATIO	14:1
POWER	125 kW (170 hp) @ 10,750 rpm
TORQUE	121 Nm (12.3 kgm) @ 8,750 rpm
FUEL INJECTION	Continental electronic fuel injection system, Øeq 46mm equivalent elliptical throttle bodies with Ride-by-Wire system
EXHAUST	Stainless steel muffler, double catalytic converter and 4 lambda probes
TRANSMISSION	
GEARBOX	6 speed with Ducati Quick Shift up/down
PRIMARY DRIVE	Straight cut gears, Ratio 1.8:1
RATIO	1=40/13, 2=36/16, 3=34/19, 4=31/21, 5=29/23, 6=27/25
FINAL DRIVE	Chain, Front sprocket z16, Rear sprocket Z42
CLUTCH	Multiplate clutch with hydraulic control. Self-servo action on drive, slipper action on over-run
CHASSIS	
FRAME	Aluminium monocoque frame
FRONT SUSPENSION	Ø50 mm fully adjustable usd fork with internal stroke sensor. Electronic compression and rebound damping adjustment with Ducati Skyhook Suspension EVO (DSS)
FRONT WHEEL	Spoked wheel 3" x 19"
FRONT TYRE	Pirelli Scorpion Trail II 120/70 R19
REAR SUSPENSION	Cantilever suspension with fully adjustable monoshock. Electronic compression and rebound damping adjustment. Electronic spring pre-load adjustment with Ducati Skyhook Suspension (DSS). Aluminium double-sided swingarm
REAR WHEEL	Spoked wheel 4,5" x 17"
REAR TYRE	Pirelli Scorpion Trail II 170/60 R17
WHEEL TRAVEL (FRONT/REAR)	200 mm - 200 mm (7,9 in - 7,9 in)
FRONT BRAKE	2 x 330 mm semi-floating discs, radially mounted Brembo Stylema 4-piston callipers, 2-pad, radial master cylinder with cornering ABS as standard equipment
REAR BRAKE	265 mm disc, 2-piston floating calliper, with cornering ABS as standard equipment
INSTRUMENTATION	6,5" TFT color display with Ducati Connect and full-map navi system
DIMENSIONS AND WEIGHTS	
DRY WEIGHT	227 kg (500 lb)
KERB WEIGHT	260 kg (573 lb)
SEAT HEIGHT	Adjustable 870 - 890 mm (34.3 - 35.0 in) 885 mm - 905 mm (34.9 in - 35.6 in) with high seat accessory 855 mm - 875 mm (33.7 in - 34.5 in) with low seat #1 accessory 825 mm - 845 mm (32.5 in - 33.3 in) with low seat #2 accessory 805 mm - 825 mm (31.7 in - 32.5 in) with low seat #2 + low suspension kit accessory
WHEELBASE	1,572 mm (61.9 in)
RAKE	24,7°
TRAIL	105,5 mm (4,15 in)
FUEL TANK CAPACITY	30.1 (7,9 US gal)
NUMBER OF SEATS	2
EQUIPMENT	
SAFETY EQUIPMENT	Riding Modes, Power Modes, cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Ducati Brake Light, Ducati Cornering Light, Vehicle Hold Control
STANDARD EQUIPMENT	Ducati Skyhook Suspension EVO, Ducati Quick Shift, Cruise control, Hands-Free, Backlit handlebar switches, 6,5" TFT colour display with Ducati Connect and full-map navigation system, Full LED headlight with DRL, Engine Brake Control (EBC), Extended Cylinder Deactivation (ECCD)
WARRANTY AND MAINTENANCE	
WARRANTY	24 months (48 months*), unlimited mileage. *Only for countries where 4ever Multistrada warranty applies.
MAINTENANCE SERVICE INTERVALS	15,000 km (9,000 miles) / 24 months
DESMO SERVICE	60,000 km (36,000 miles)
EMISSIONS AND CONSUMPTION (ONLY FOR COUNTRIES WHERE EURO 5 STANDARD APPLIES)	
STANDARD	Euro 5
CO2 EMISSIONS	152 g/km
CONSUMPTION	Data under revision

Bike specifications and equipment may vary from market to market. Please refer to your local dealer for further information